

Furon® 1" Static Mixer



Efficient Mixing of Liquid Media with No Moving Parts

Furon®'s Static Mixer offers an innovative and efficient means of mixing two or more chemistries with minimal pressure loss. Its compact, inline design allows for easy installation into existing pipelines. Our Static Mixer contains no moving parts, assuring low operating costs and long life. Internal mixing components are removable, allowing for easy maintenance and cleaning. Outlet end connection types and sizes can be easily changed to accommodate a variety of piping configurations. All components are constructed from 100% virgin PTFE and high-purity PFA, making the Furon® Static Mixer ideal for use with both ultra-pure and high corrosive chemistries. In addition, our Static Mixer is 100% metal free, eliminating the potential for ionic contamination.

Features/Benefits

- Mixes two or more chemistries with no moving parts
- Ideal for high purity mixing applications
- Low pressure drop (< 4 psi @ 7.9 GPM; < 11 psi @ 13.2 GPM)
- Constructed from 100% virgin PTFE and high-purity PFA
- Flow rates up to 13.2 GPM
- Internal mixing components removable for easy cleaning and maintenance
- Innovative, compact design

Typical Applications

- Mixing of wet ingredients in chemical processing and manufacturing operations
- Blending catalyst, dye, or additive into a liquid media
- Dilution of solvents and aggressive chemicals
- pH control
- Mixing of chemicals in Semiconductor and Photovoltaic wet processes


Furon® 1" Static Mixer

Ordering Information


Part No.	End Connection	Cv	Max. Flow Rate
SM1-F16-F16-T	1" Flare	4.1	13.2 GPM (50 L/min)

Specifications And Performance

- Flow Rate: 13.2 GPM (50 L/min) maximum @ 60 PSIG inlet
- Maximum pressure drop:
 - 3.16 PSID @ 7.9 GPM
 - 10.0 PSIG @ 13.2 GPM
- Cv flow factor: 4.0
- Media operating temperature: 41°F to 180°F (5°C to 100°C)
- Media operating pressure: 90 PSIG max at room temperature
- Material:
 - High-purity PTFE, PFA and Fluoroloy®-T



**1" Static Mixer
Delta P vs. Flow Rate**



DI Inlet pressure set up: 60 PSIG at room temp. @72° F

Saint-Gobain Performance Plastics-USA

High Purity Systems
7301 Oranewood Avenue
Garden Grove, CA 92841-1411
Phone: (714) 630-5818
Fax: (714) 688-2614
USA Toll Free: (800) 833-5661

Saint-Gobain Performance Plastics-France

High Purity Systems
EADAC des Berthilliers
71850 Charnay les Macons
France
Phone: +33(0)3 85 20 27 00
Fax: +33 (0)3 85 29 18 48



Furon® is a registered trademark.
Fluoroloy® is a registered trademark.

12-month **Limited Warranty:** For a period of 12 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product to be free from defects in manufacturing. This company's only obligation will be to provide replacement product for any material proven to have such a defect, or at SGPPL's option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct, consequential or incidental, arising out of the use, misuse, or inability to use this product. SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Saint-Gobain Performance Plastics reserves the right to change product specifications without prior notice.

NOTE: Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product or of any final product into which the product may be incorporated by the purchaser and/or user.